



VideoScope Plus



2 m
DOF 3...7 cm

Compact inspection camera
for visual inspections of areas
which are difficult to access
– featuring record function

Rev0316



Camera head (ø 9 mm)

3,5" TFT colour display
with LED-Lighting

- **The camera head at a FlexCamera** transfers pictures directly to a LCD-Monitor.
- **Problem locating:** the camera indicates what is behind or in objects, walls circuits or cables etc. even under worst light conditions, due to the LED-lighting.
- **REC-Function:** still picture and video can be **recorded** for a later analysis.
- **Waterproof camera head and cable**
- **Ideal for difficult accessible areas** due to the small measuring head (ø 9 mm)
- **Diversified application** with 2 m camera.
- Powerful object lighting thanks to **4 high-performance LEDs**
- **Extraneous light reduction:** contrasty LC-Display which provides an optimum display even under light irradiation.
- External monitors operated via **TV Out connection**
- **Formattable SDHC-Card**
- **Rotation:** The manual image rotation function enables the image to be rotated by 180° on the monitor.

TECHNICAL DATA

CAMERA HEAD

ø 9 mm, water-resistant, IP 67

CAMERA FOCUS

F3 cm - F7 cm

SCREEN TYPE

3,5" TFT colour display

CAMERA RESOLUTION

640 x 480 pixels

DISPLAY RESOLUTION

320 x 240 pixels

IMAGE / VIDEO RESOLUTION

720 x 480 pixels

IMAGE FORMAT / VIDEO FORMAT

JPEG / AVI

LED

10 brightness levels

ZOOM

1.5x digital zoom in 10% increments

MEMORY

Supports up to max. 8 GB SDHC card

PORT

Mini USB

CONNECTIONS

Micro-SD, Analog-video

LENGTH OF FLEX CABLE

2 m

POWER SUPPLY

4 x AA 1.5 V batteries

OPERATING TEMPERATURE

0 °C ... 45 °C

STORAGE TEMPERATURE

-10 °C ... 60 °C

WEIGHT

(incl. batteries) 0,58 kg



VideoScope Plus

+ batteries
+ USB cable

Packing dimension (W x H x D)
175 x 300 x 150 mm

ARTICLE	ARTICLE NO.	EAN CODE	PU
VideoScope Plus	082.254A	4 021563 691289	2

CAMERA	640 x 480 pixel	LED LIGHT	IP 67
DISPLAY	320 x 240 pixel	3,5" LCD	180° ZOOM 1,5x

REC	SD	USB	VIDEO OUT	4 x AA
-----	----	-----	-----------	--------